



# HC140

## SPECIFICATIONS

### BATTERY DESIGN

- Absorbent glass mat (AGM) technology
- 12V battery VRLA
- Can be mounted in any orientation except inverted.
- US DOT and IATA certified non-spillable
- Sealed Construction (Non-Spillable Battery)
- Can be choose to fitted with TP brass automotive terminal
- Long Service Life
- Shipped fully charged - just install and go!

### PERFORMANCE FEATURES

- PHCA: 2400A at 80°F (27°C) for 5 seconds
- PCCA: 1500A at 0°F (-18°C) for 5 seconds
- CCA: 1210A at 0°F (-18°C)
- CA/MCA: 1505A at 32°F (0°C)
- HCA: 1750A at 80°F (27°C)
- Reserve capacity: 321 minutes
- Short circuit current: 5000A
- Operation temperature range:  
-5°F (-15°C) to 122°F (50°C)

### Nominal Dimensions

Length		Width		Height		Total Height		Weight	
mm	in	mm	in	mm	in	mm	in	kg	pound
327	12.87	182	7.17	269	10.59	273	10.75	44.2	97.44

### HIGH RATE DISCHARGE AT 77°F (25°C)

5 sec.	10 sec.	20 sec.	30 sec.
2400A	2155A	1880A	1750A

### EXTENDED DISCHARGE AT 77°F (25°C) TO 10.02V

5min	15min	1hr	3hr	5hr	10hr	20hr
461A	237A	85A	36.5A	24A	13.4A	7.20A

### PHYSICAL CHARACTERISTICS

